


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

			REVISIONS REVISIONS			
D	REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED


ASSY QTY	ASSY QTY	B/O	Part #	QTY.	Description	Material	b/O information or specifications	PG.
			-1	1	MAIN FRAME		RB T102012-1	1
			-3	1	FRONT PIVOT SUPPORT ASSEMBLY		RB T102012-3	1
	Χ		-5	1	LIFT ARM WELDMENTS		RB T102012-5	1
	1		-7		TOW BAR ARMS UPPER ASSEMBLY			1
	1		-9		TOW BAR ARMS LOWER ASSEMBLY			1
	1		-11		REAR ARM ASSEMBLY			1
	1		-13		REAR ARM STABILIZER ASSEMBLY			1
			-15	1	TOW SIDE LIFT		RB T102012-15	1
			-17	1	REAR LIFT ASSEMBLY		RB T102012-17	1
			-19	1	TOW BAR ASSEMBLY		RB T102012-19	1
		B/O	-195	8	HEX NUT	STEEL	5/16-18 (MCMASTER-CARR #95462A030)	1
		B/O	-197	8	WASHER	STEEL	Ø5/16 (MCMASTER-CARR #95229A450)	1
		B/O	-291	2	HEX HEAD CAP SCREW	STEEL	1/2-20 X 2 (MCMASTER-CARR #91257A748)	1
		B/O	-293	20	WASHER	STEEL	Ø1/2 I.D. (MCMASTER-CARR #90126A033)	1
		8/0	-295	18	HEX NUT	STEEL	1/2-20 (MCMASTER-CARR #94895A825)	1
			-323	2	MAIN FRAME 1 PIVOT PLATE	A36/1018/1020 HR		3
			-325	1	PIVOT ROD	4140/4142		4
			-327	2	PIVOT ROD SLEEVE	A513		5
		B/O	-329	2	ROLL PIN	STEEL	Ø1/8 X 1-1/4 (MCMASTER-CARR #90692A701)	1
		B/O	-331	8	BOLT	STEEL	3/8-24 X 1 (MCMSTER-CARR #92865A215)	1
		B/O	-333	22	FLANGE BEARING	BRONZE	SYMCO #SF-1420-10	1
			-335	4	CASTER ASSY		RB T102012-335	1
		B/O	-337	2	WASHER	STEEL	Ø1 (MCMASTER-CARR #90108A038)	1
		B/O	-339	4	BOLT	STEEL	5/8-18 X 5-1/2 (MCMASTER-CARR #91247A449)	1
		B/O	-341	4	WASHER	STEEL	Ø5/8 (MCMASTER-CARR #90126A035)	1
		B/O	-343	4	NYLOCK NUT	STEEL	5/8-18 (MCMASTER-CARR #95615A260)	1
		B/O	-345	2	ROD END		MCMASTER-CARR #60645K161	1
		B/O	-347	8	BOLT	STEEL	5/16-18 x 1-1/4 (MCMASTER-CARR #92865A585)	1
		B/O	-349	2	HYDRAULIC PUMP		ENERPAC P80 MSC #80021603	1
		B/O	-351	1	HYDRAULIC CYLINDER		PRINCE #B200180ABAAA07B	1
		B/O	-353	16	BOLT	STEEL	1/2-20 X 1-1/2 (MCMASTER-CARR #92620A746)	1
		B/O	-355	1	HYDRAULIC CYLINDER		PRINCE # B200100ABAAA07B	1
		B/O	-357	2	FLOW CONTROLLER		PRINCE # WFC-600	1
		B/O	-361	2	STRAP	RED NYLON WEBBING	90" X 1.5" (STAN'S UPHOLSERY)	6
		B/O	-363	11	HOSE CLAMP	STEEL	Ø3/4 (MCMASTER-CARR #3225T6)	1
		B/O	-365	11	STANDOFF	STEEL	1/4-20 X 3/4 (MCMASTER-CARR #93620A194)	1
		B/O	-367	2	ADAPTER FITTING	STEEL	MALE 3/4-16 UNF TO MALE 3/8" NPTF (MCMASTER-CARR # 50925K331)	1
		B/O	-369	1	PIPE NIPPLE	304 S.S.	3/8 NPT X 3-1/2 (MCMASTER-CARR #46755K133)	1
		B/O	-371	1	PIPE NIPPLE	316 S.S.	3/8 NPT X 2 (MCMASTER-CARR #4475K33)	1
		B/O	-373	2	ELBOW	STEEL	FEMALE TO FEMALE 3/8 NPTF (MCMASTER-CARR #50925K153)	1
		B/O	-375	11	SCREW	S.S.	1/4-20 X 1/2 (MCMASTER-CARR #91772A537)	1
		B/O	-377	2	45° ELBOW	STEEL	MALE 3/8" NPTF TO FEMALE 3/8" NPTF (MCMASTER-CARR # 50925K181)	1
		B/O	-379	_	LOWER FRONT HOSE ASSY		MALE 3/8 NPTF END FITTINGS, Ø 3/4, 130 IN LENGTH	1
		B/O	-381	2	SWIVEL FITTING	STEEL	MALE 3/8" NPTF TO FEMAILE 3/8" NPT (MCMASTER-CARR # 5340K36)	1
		B/O	-383	1	REAR HOSE ASSEMBLY		MALE 3/8 NPTF END FITTINGS, Ø 3/4, 98 IN LENGTH	1
		B/O	-385		BOLT	STEEL	7/16-20 x 3 (MCMASTER-CARR #91257A704)	1
		B/O	-387	11	WASHER	STEEL	Ø7/16 (MCMASTER-CARR #95229A520)	1
		B/O	-389		NYLOCK NUT	STEEL	7/16-20 (MCMASTER-CARR #95615A190)	1
		B/O	-391		PIN W/ HAIRPIN	STEEL	1/2 x 1-1/4 (MCMASTER-CARR # 97245A709)	1
	ASSY							\vdash






SUPPORT DOLLY, TAILBOOM


DWG NO.		RB	T1	02012		1		
MAT'L HEAT TREAT FINISH SPEC				DIME .XXX ± .005 .XX + .01 .X ± .1 1. BREAK AL	L SHARP EDGES	s		
DRAWN BY:	GILBER1	-		.015 x 45° C	OR .015R NAL LIMITS APPLY			
CHECKED:	CLOUGH	1		AFTER PLA	ATING			
OPPS APPR:	ANDERS	ON		ASME Y14.	T DIM AND TOL PER 5M-2009			
QA APPR:	QA APPR: LINDSAY				USED ON MODEL			
APPROVED:	GILBER1	-		212, 2	212, 214B, 214ST, & 412			
SCALE .	1:46 DATE 3			27/2014	SHEET 2 OF	6		



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED







SUPPORT DOLLY, TAILBOOM

DWG NO. RB T102012-325 MAT'L 4140/4142 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ± .5°

.X ± .1 SURFACES = 125/ HEAT RC 28-34
TREAT RC 28-34
FINISH ZINC PLATE SPEC ASTM B633 TYPE I SC 2 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: GILBERT CHECKED: CLOUGH


OPPS APPR: ANDERSON QA APPR: LINDSAY USED ON MODEL APPROVED: GILBERT 212,214B,214ST, & 412


SCALE 1:3 3/26/2014 SHEET 4 OF 6


PIVOT ROD

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

		REVISIONS REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED









SUPPORT DOLLY, TAILBOOM

RB T102012-327 MAT'L A513 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ± .5°

.X ± .1 SURFACES = 125/ HEAT TREAT FINISH POWDER COAT YELLOW SPEC FED #13538 DRAWN BY: GILBERT CHECKED: CLOUGH OPPS APPR: ANDERSON QA APPR:

DWG NO.

1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 LINDSAY USED ON MODEL APPROVED: GILBERT 212,214B,214ST, & 412 SCALE 1:1 3/26/2014 SHEET 5 OF 6

PIVOT ROD SLEEVE

